



OCEAN SAFETY®

datasheet

Automatic powder fire extinguishers



FIR0480

1 kg Automatic powder

FIR0485

2 kg Automatic powder

Details

Commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

The unit required is determined by the floor area of that compartment. Only one unit should be installed in any one compartment and should provide the total protection required for that compartment.

- Compact and economical auto extinguisher
- Manufacturer's 5 year warranty
- Stored pressure - Easy low cost maintenance
- Safe for use on electrical equipment
- Suitable for A,B & C class fires
- Brass valve - Easy to read pressure gauge
- Powder coated, steel wire bracket



wood, paper, textiles



flammable liquids



flammable gas



electrical risks

Manufactured in the UK under ISO 9001:2000 Quality Management System

Model	FIR0480	FIR0485
Capacity	1 kg	2 kg
Total Weight	2.14 kg	3.6 kg
Total Height	330 mm	380 mm
Total Width (including bracket)	95 mm	125 mm
Working Temp.	-20 to +60 °C	-20 to +60 °C
Discharge Time	Under 10 secs @ 79°C	Under 10 secs @ 79°C
Operating Pressure	12 bar @ 20°C	12 bar @ 20°C
Minimum Burst Pressure	55 bar	55 bar
Maximum area protected	1.0m ³	2.0m ³

Description	Partnumber
1 kg Automatic fire extinguisher	FIR0480
2 kg Automatic fire extinguisher	FIR0485

Your Life Saving Supplier

Ocean Safety Ltd, Saxon Wharf, Lower York Street, Southampton, SO14 5QF

Tel: +44(0) 2380 720 800 Fax: +44(0) 2380 720 801

www.oceansafety.com email: info@oceansafety.com

oceansafety.com