



1nm tri-color/anchor/strobe, black anodized

101-009G2S-B

1nm tri-color/anchor/strobe, black anodized
Horizontally mounted with 0,75m cable

Specifications	
Number	101-009G2S-B
Light Color	Red,Green,White
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 2.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438011960
IP rating	IP68
UPC Code	879343011963
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150
Current consumption (mA @ 24VDC)	81
Vessel size	Under 12M

Specifications

Weight (Kg) 0.73 Kg

Weight (Oz) 25.75 Oz