



2nm 360° white, silver anodized, with 0,7m cable.

200-012G2

2nm 360° white, silver anodized

- LED (Light Emitting Diode) navigation light.
- Unique and precise definition of light angles.
- Rugged and unbreakable: Precision machined anodised aluminium housing protects the LED's and electronics.
- Completely waterproof and vibrationproof: Interior is fully filled and sealed with special potting resin.
- Waterproof to IP 68+ (submersible).
- Low power consumption – 70 to 90% less than traditional navigation lights.
- Full brightness with input voltages ranging from 10 to 32 Volts.
- All Lopolights have been tested several times during production, a total of more than 24 hours.
- Easy to install, adaptor and screws included (when applicable).

Specifications	
Number	200-012G2
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012011
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343012014
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	167
Stock status	Usually in stock
Lead time	1-2 weeks
Current consumption (mA @ 24VDC)	110
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.53 Kg
Weight (Oz)	18.69 Oz